

Serial (RS-232)

Need Assistance? Call 480-641-9733 7:30 to 2:30 PST. Let us help!
 Be sure to set "Page Scaling" to "None" in printer setup.

INSERT THIS SIDE UP, THIS END FIRST
 USE BLACK INK, FILL OVALS COMPLETELY

section 1

Pulse/Serial
 \$185 Credit Lines
 \$120 Credit Lines
 MDB
 RS-232 Always Enabled
 Parallel HI
 Special 1
 Special 2

Select only one interface Type

section 2

64
 32
 16
 8
 None

Example: For 50 ppd, fill in the ovals for 32, 16, and 2. (32+16+2 = 50)

Pulses per Dollar (sum of selected values)

Pulse Speed: Slow Fast

Lighted Bezel: Solid On Flashing

section 3

Bill 1 (\$1) Bill 2 (\$5)
 Bill 3 (\$10) Bill 4 (\$20)
 Bill 5 (\$50) Bill 6 (\$100)
 Bill 7 Bill 8
 Bill 9 Bill 10
 Bill 11 Bill 12

Example: To accept USA \$1, \$5, and \$10, fill in the ovals for Bill 1, Bill 2, and Bill 3.

Security Level: High Low

Insert Direction: Face up, Left 1st All 4 Ways

section 4

Select Bills to Enable

section 5

This Configuration Card should be printed on standard copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).
 If printing from a .PDF file, turn off the "shrink to fit" option in your printer settings for proper scale.

Serial RS-232

INSERT THIS SIDE UP, THIS END FIRST
 USE BLACK INK, FILL OVALS COMPLETELY

section 1

Pulse/Serial
 \$185 Credit Lines
 \$120 Credit Lines
 MDB
 RS-232 Always Enabled
 Parallel HI
 Special 1
 Special 2

Select only one interface Type

section 2

64
 32
 16
 8
 None

Example: For 50 ppd, fill in the ovals for 32, 16, and 2. (32+16+2 = 50)

Pulses per Dollar (sum of selected values)

Pulse Speed: Slow Fast

Lighted Bezel: Solid On Flashing

section 3

Bill 1 (\$1) Bill 2 (\$5)
 Bill 3 (\$10) Bill 4 (\$20)
 Bill 5 (\$50) Bill 6 (\$100)
 Bill 7 Bill 8
 Bill 9 Bill 10
 Bill 11 Bill 12

Example: To accept USA \$1, \$5, and \$10, fill in the ovals for Bill 1, Bill 2, and Bill 3.

Security Level: High Low

Insert Direction: Face up, Left 1st All 4 Ways

section 4

Select Bills to Enable

section 5

This Configuration Card should be printed on standard copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).
 If printing from a .PDF file, turn off the "shrink to fit" option in your printer settings for proper scale.

Serial RS-232

INSERT THIS SIDE UP, THIS END FIRST
 USE BLACK INK, FILL OVALS COMPLETELY

section 1

Pulse/Serial
 \$185 Credit Lines
 \$120 Credit Lines
 MDB
 RS-232 Always Enabled
 Parallel HI
 Special 1
 Special 2

Select only one interface Type

section 2

64
 32
 16
 8
 None

Example: For 50 ppd, fill in the ovals for 32, 16, and 2. (32+16+2 = 50)

Pulses per Dollar (sum of selected values)

Pulse Speed: Slow Fast

Lighted Bezel: Solid On Flashing

section 3

Bill 1 (\$1) Bill 2 (\$5)
 Bill 3 (\$10) Bill 4 (\$20)
 Bill 5 (\$50) Bill 6 (\$100)
 Bill 7 Bill 8
 Bill 9 Bill 10
 Bill 11 Bill 12

Example: To accept USA \$1, \$5, and \$10, fill in the ovals for Bill 1, Bill 2, and Bill 3.

Security Level: High Low

Insert Direction: Face up, Left 1st All 4 Ways

section 4

Select Bills to Enable

section 5

This Configuration Card should be printed on standard copy paper, measuring 6.0 x 2.6 inches (152 x 66 mm).
 If printing from a .PDF file, turn off the "shrink to fit" option in your printer settings for proper scale.

Serial RS-232